DOCKET NO.: LEUCA 13-8

WE CLAIM:

	1.	A system	m for managing the routing of information from a source
to a desti	nation thro	ugh a plu	rality of networks, wherein at least one of said networks
is a packe	et network,	said syst	em comprising:

a routing processor for receiving a routing query signal from said source, said signal specifying said destination to which said information will be routed; and

a memory for storing at least one characteristic of said source; said memory storing at least one characteristic of said destination;

wherein said processor determines a route for the transmission of said information based on said routing query signal and on said characteristics stored in said memory.

2. The system according to claim 1, wherein a characteristic of said destination includes information relating to the equipment at said destination.

- 3. The system according to claim 1, wherein said source subscribes to a fixed wireless service network.
- 4. The system according to claim 3, wherein said destination subscribes to the same fixed wireless service network as said source.
- 5. The system according to claim 3, wherein said destination subscribes to a PSTN service network.



18

19

15

16

17

1

2

3

4

5

6

7

- 338611_1

DOCKET NO.: LEUCA 13-8

1	6. The system according to claim 1, wherein a characteristic of said
2	destination includes information identifying the service to which said destination
3	subscribes.
4	7. The system according to claim 1, wherein said information
5	includes digitized voice information.
6	8. The system according to claim 1, wherein said signal is a DTMF
\ \\.	signal.
8000	9. A system for routing information to a destination, said system
	comprising:
<u>P</u>	a plurality of networks, wherein at least one of said networks is a
	packet network and wherein each network is linked to at least one other network by a
12	communication medium; and
10 112 13 14 15	a routing processor for receiving a routing query signal, said routing
<u> </u>	query signal, including at least one characteristic of said destination, said routing
15	processor determining a transmission path for routing said information through said
16	plurality of networks;
17	wherein said routing processor determines said transmission path based
18	on said routing query signal and on said received characteristics.
19	10. The system according to claim 9, wherein said destination
20	subscribes to a fixed wireless service network.

DOCKET NO.: LEUCA 13-8

2
3
4
5
6 \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\
8
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
16
17
18
10

1

11.	The system	according	to claim 9,	wherein s	aid destination
subscribes to a PST	'N service netv	ork.			

- 12. The system according to claim 9, wherein said characteristics of said destination identify the type of service to which said destination subscribes.
- destination through a plurality of networks, wherein at least one of said networks is a packet network, each network being linked to at least one other network by a communication medium, said method comprising the steps of:

receiving a routing query specifying a destination to which said information will be routed at a routing processor;

storing at least one characteristic of said destination; and determining a route for the transmission of said information based on said routing query and on said stored characteristics.

- 14. The method according to claim 13, wherein said step of storing characteristics includes the step of storing at least one address for said destination.
- 15. The method of claim 13, wherein said step of determining includes the step of identifying the subscriber service of said destination.
- 16. The method for managing the routing of information to a destination through a plurality of networks, wherein at least one of the networks is a

DOCKET NO.: LEUCA 13-8

19

20

packet network and wherein each network is linked to at least one other network by a communication medium, said method comprising the steps of:

receiving a routing query signal from a source of one of said networks and information concerning at least one characteristic of said destination; and determining a transmission path for routing said information through said networks, said transmission path comprising at least one network in addition to said packet network, wherein said step of determining is based on said received routing query signal and on said received characteristics.

17. A method for managing the routing of information to a destination through a plurality of networks wherein at least one of the networks is a packet network and wherein each network is linked to at least one other network by a communication medium, said method comprising the steps of:

receiving a routing query signal including routing requirements from a source; and

determining a transmission path for routing said information through said networks, wherein said transmission path comprises network elements of at least one of said networks in addition to network elements of said packet network.

18. The method according to claim 17, wherein said step of determining a transmission path includes the step of identifying the subscriber service of said destination.

17

1

19. A method for managing the routing of information from a subscriber of a fixed wireless service network to a destination through a plurality of networks, wherein at least one of said networks is a packet network and wherein each network is linked to at least one other network by a communication medium, said method comprising the steps of:

receiving a routing query signal from said subscriber of said fixed wireless service network;

storing information concerning at least one characteristic of said destination at a routing processor;

determining a transmission path for routing said information through said networks, said transmission path comprising elements of at least one of said networks in addition to elements of said packet network, wherein said step of determining said transmission path is based on said routing query and said stored characteristics;

sending a routing response signal from said routing processor to said subscriber; and

routing said information over said path.

338611_1